

MGBS Furnace Comparison Chart

	<b>Curb Weight (Approximate)</b>	<b>Foot Print (Assembled w/ Accessories)</b>	<b>Dimensions (Disassembled/ no accessories)</b>	<b>Max. Working Dimension (Main Port)</b>	<b>Max. Working Dimension (Side Port)</b>	<b>Included Standard Crucible Size</b>	<b>Alternative Crucible Size Options</b>
<b>Mini Dragon</b>	180 pounds (82 kg)	48" D x 48" W x 81" H (122cm x 122cm x 206cm)	16" D x 16" W x 52" H* (41cm x 41cm x 132cm)	7" H x 7" W x 11.5" D (17.8cm x 17.8cm x 29 cm)	—	15 lb. (7 kg)	—
<b>Baby Dragon</b>	550 pounds (249 kg)	90" D x 48" W x 78" H (229cm x 122cm x 198cm)	34" D x 31" W x 56" H (87cm x 79cm x 143cm)	8" H x 8" W x 16" D (21cm x 21cm x 41 cm)	—	30 lb. (13 kg)	40 lbs. (18kg)
<b>Double Baby Dragon</b>	550 pounds (249 kg)	90" D x 90" W x 78" H (229cm x 229cm x 198cm)	34" D x 31" W x 56" H (87cm x 79cm x 143cm)	8" H x 8" W x 16" D (21cm x 21cm x 41 cm)	8" H x 8" W x 16" D (21cm x 21cm x 41 cm)	30 lb. (13 kg)	40 lbs. (18kg)
<b>Little Dragon</b>	850 pounds (385 kg)	90" D x 48" W x 78" H (229cm x 122cm x 198cm)	34" D x 31" W x 56" H (87cm x 79cm x 143cm)	9" H x 9" W x 20" D (23cm x 23cm x 51 cm)	—	60 lbs. (27 kg)	95 lbs. (43 kg)
<b>Double Little Dragon</b>	850 pounds (385 kg)	90" D x 90" W x 78" H (229cm x 229cm x 198cm)	34" D x 31" W x 56" H (87cm x 79cm x 143cm)	9" H x 9" W x 20" D (23cm x 23cm x 51 cm)	8" H x 8" W x 20" D (21cm x 21cm x 51 cm)	60 lbs. (27 kg)	95 lbs. (43 kg)
<b>Big Dragon</b>	850 pounds (385 kg)	90" D x 48" W x 78" H (229cm x 122cm x 198cm)	34" D x 31" W x 56" H (87cm x 79cm x 143cm)	12" H x 12" W x 20" D (30cm x 30cm x 51 cm)	—	95 lbs. (43 kg)	—
<b>Double Big Dragon</b>	850 pounds (385 kg)	90" D x 90" W x 78" H (229cm x 229cm x 198cm)	34" D x 31" W x 56" H (87cm x 79cm x 143cm)	12" H x 12" W x 20" D (30cm x 30cm x 51 cm)	8" H x 8" W x 20" D (21cm x 21cm x 51 cm)	95 lbs. (43 kg)	—
<b>Phoenix</b>	750 pounds (340 kg)	60" D x 31" W x 56" H (152cm x 79cm x 143cm)	47" D x 31" W x 56" H (120cm x 79cm x 143cm)	12" H x 14" W x 19" D (30cm x 36cm x 48cm)	—	—	Crucibles sold separately. Multiple configurations available***

\*The Mini Dragon can detach from its base, for more compact transportation and storage.

\*\*\*The Phoenix does not come with a crucible. However, it has the capacity for a variety of configurations in both freestanding and invested modules. For all the possibilities, please see the Phoenix Crucible Options document.

MGBS Furnace Comparison Chart

	Gas Type	Gas Pressure	Gas Use (Propane)	Gas Use (Natural Gas)	BTU/hr Range	Avg. Heat Up Time (Propane)**	Avg. Heat Up Time (Natural Gas)**
<b>Mini Dragon</b>	Propane or Natural Gas	11 wci (27mbar) recommended 7 wci (17mbar) min. 14 wci (35mbar) max.	+/- 0.5 gallons per hour (+/- 1.1 kg per hour)	+/- 46 ft <sup>3</sup> per hour (+/-1.4 m <sup>3</sup> per hour)	10,000 - 60,000	3 hours	4 hours
<b>Baby Dragon</b>	Propane or Natural Gas*	11 wci (27mbar) recommended 7 wci (17mbar) min. 14 wci (35mbar) max.	+/- 1 gallon per hour (+/- 2.2 kg per hour)	+/- 93 ft <sup>3</sup> per hour (+/- 2.63 m <sup>3</sup> per hour)	60,000 - 140,000	3.5 hours	4.5 hours
<b>Double Baby Dragon</b>	Propane or Natural Gas*	11 wci (27mbar) recommended 7 wci (17mbar) min. 14 wci (35mbar) max.	+/- 1 gallon per hour (+/- 2.2 kg per hour)	+/- 93 ft <sup>3</sup> per hour (+/- 2.63 m <sup>3</sup> per hour)	60,000 - 140,000	3.5 hours	4.5 hours
<b>Little Dragon</b>	Propane or Natural Gas*	11 wci (27mbar) recommended 7 wci (17mbar) min. 14 wci (35mbar) max.	+/- 1 to 1.5 gallon per hour (+/- 2.2 to 3.3 kg per hour)	+/- 93 to 140 ft <sup>3</sup> per hour (+/- 2.6 to 4.0 m <sup>3</sup> per hour)	60,000 - 150,000	4 hours	5 hours
<b>Double Little Dragon</b>	Propane or Natural Gas*	11 wci (27mbar) recommended 7 wci (17mbar) min. 14 wci (35mbar) max.	+/- 1 to 1.5 gallon per hour (+/- 2.2 to 3.3 kg per hour)	+/- 93 to 140 ft <sup>3</sup> per hour (+/- 2.6 to 4.0 m <sup>3</sup> per hour)	60,000 - 150,000	4 hours	5 hours
<b>Big Dragon</b>	Propane or Natural Gas*	11 wci (27mbar) recommended 7 wci (17mbar) min. 14 wci (35mbar) max.	+/- 1 to 2 gallon per hour (+/- 2.2 to 4.4 kg per hour)	+/- 93 to 186 ft <sup>3</sup> per hour (+/- 2.6 to 5.3 m <sup>3</sup> per hour)	60,000 - 150,000	5 hours	6 hours
<b>Double Big Dragon</b>	Propane or Natural Gas*	11 wci (27mbar) recommended 7 wci (17mbar) min. 14 wci (35mbar) max.	+/- 1 to 2 gallon per hour (+/- 2.2 to 4.4 kg per hour)	+/- 93 to 186 ft <sup>3</sup> per hour (+/- 2.6 to 5.3 m <sup>3</sup> per hour)	60,000 - 150,000	5 hours	6 hours
<b>Phoenix</b>	Propane or Natural Gas*	11 wci (27mbar) recommended 7 wci (17mbar) min. 14 wci (35mbar) max.	+/- 1 to 2 gallon per hour (+/- 2.2 to 4.4 kg per hour)	+/- 93 to 186 ft <sup>3</sup> per hour (+/- 2.6 to 5.3 m <sup>3</sup> per hour)	60,000 - 150,000	4-5 hours	5-6 hours

\* These models of furnaces can also be fit with a Waste Veggie Burner system from Organic Combustion Systems. The Waste Veggie Burner System is sold separately. Estimate fuel usage on a Waste Veggie Burner System is 1 to 2 gallon of vegetable oil/hour.

\*\* Times are approximate and will vary based on a number of factors.

MGBS Furnace Comparison Chart

	Burner Type	Burner Safety Standard	Burner Safety Additional Options	Recommended Max. Operating Temp	Electrical Use	Preheat Hose Option Availability
<b>Mini Dragon</b>	Ceramic 2.5" Top Fired	Proof of Air	Proof of Flame	2350 °F (1288 °C)	Blower is 120V AC, 1A-5A (240V available)	
<b>Baby Dragon</b>	Ceramic Top Fired	Proof of Air	Proof of Flame, Comprehensive	2375 °F (~1301 °C)	Blower is 120V AC, 1A-5A (240V available)	
<b>Double Baby Dragon</b>	Ceramic Top Fired	Proof of Air	Proof of Flame, Comprehensive	2375 °F (~1301 °C)	Blower is 120V AC, 1A-5A (240V available)	
<b>Little Dragon</b>	Ceramic Top Fired	Proof of Air	Proof of Flame, Comprehensive	2375 °F (~1301 °C)	Blower is 120V AC, 1A-5A (240V available)	<input checked="" type="checkbox"/>
<b>Double Little Dragon</b>	Ceramic Top Fired	Proof of Air	Proof of Flame, Comprehensive	2375 °F (~1301 °C)	Blower is 120V AC, 1A-5A (240V available)	<input checked="" type="checkbox"/>
<b>Big Dragon</b>	Ceramic Top Fired	Proof of Air	Proof of Flame, Comprehensive	2375 °F (~1301 °C)	Blower is 120V AC, 1A-5A (240V available)	<input checked="" type="checkbox"/>
<b>Double Big Dragon</b>	Ceramic Top Fired	Proof of Air	Proof of Flame, Comprehensive	2375 °F (~1301 °C)	Blower is 120V AC, 1A-5A (240V available)	<input checked="" type="checkbox"/>
<b>Phoenix</b>	Pine Ridge Ribbon Side Fired*	Proof of Air	Proof of Flame, Comprehensive, Auto Control	2375 °F (~1301 °C)	Variable Speed Blower is 120V AC, 5A (240V available)	

\* On Phoenix Comprehensive and Auto Control options, burner is a Direct Fire Phoenix VH015

MGBS Furnace Comparison Chart

Included Accessories

	Accessory Port(s)	Lift Handles	Push/Pull Bar	Double Yoke Holder	Mini Marver 16" x 8"	Pipe Warmer	Pipe Hanger	Propane Gas Feed Package	Door
Mini Dragon	1	☑		☑	☑	☑	☑	☑	One Half Moon
Baby Dragon	2		☑	☑	☑	☑	☑	☑	One Half Moon
Double Baby Dragon	1		☑	☑☑	☑☑	☑☑	☑	☑	Two Half Moon
Little Dragon	2		☑	☑	☑	☑	☑	☑	One Half Moon
Double Little Dragon	1		☑	☑☑	☑☑	☑☑	☑	☑	Two Half Moon
Big Dragon	2		☑	☑	☑	☑	☑	☑	One Half Moon
Double Big Dragon	1		☑	☑☑	☑☑	☑☑	☑	☑	Two Half Moon
Phoenix	1		☑	☑				☑	Two Half Moon & One Heat-up

